

The Vito 114 CDI Panel Van

(Pro Version)

INTERIOR

INTERIOR	
Comfort overhead control panelLED light strip in load compartment	Instrument cluster with pixel matrix displayWooden flooring in the rear
EXTERIOR	
Bumpers body parts painted body colourLED tail lamps	Light alloy wheels
COMFORT	
Height and rake adjustable steering wheel	Multifunction steering wheel with trip
 Air conditioning system, driver's cabin 	computer
 Sliding door, left and right 	 Comfort driver's seat
• Hill-Start Assist	Reversing camera
SAFETY	
• Windows in tailgate / rear door with wipe /	• LED Intelligent Light System Headlight
wash system	assistant
 Airbag for driver and front passenger 	Rain sensor
 3-point safety belt 	 ATTENTION ASSIST drowsiness detection
	Comfort overhead control panel LED light strip in load compartment EXTERIOR Bumpers body parts painted body colour LED tail lamps COMFORT Height and rake adjustable steering wheel Air conditioning system, driver's cabin Sliding door, left and right Hill-Start Assist SAFETY Windows in tailgate / rear door with wipe / wash system Airbag for driver and front passenger



The Mercedes-Benz Vito purchased from Cycle & Carriage Industries Pte Limited is entitled for the Comprehensive Maintenance Package, unless otherwise stated.

It covers mechanical, electrical as well as wear and tear items for 5 years or 150,000 km, whichever comes first. Terms and conditions apply.

Effective Date: 5 October 2021




Vehicle dimensions (mm)

Legend for illustration: All details in mm. Turning circle Ø approx. 11.8 m, track circle Ø approx. 11.1 m. 1 Vehicle height in conj. with optional roof rails + 48 mm. 2 Interior height. 3 Unladen.

- ⁴ Maximum width of load / passenger compartment (measured on floor). ⁵ Clearance between the wheel arches. ⁶ Dimensions measured on vehicle floor. ⁷ 2060 with exterior mirrors folded in.
- Information in accordance with the version of Directive 92/21/EC applicable at time of going to print. (With driver 68 kg, luggage 7 kg, all service fluids and fuel tank 90% full). Equipment and/or equipment lines may produce an increase / decrease in the GVW and thus influence the payload.
- 2. Combined. The figures shown were obtained in accordance with the prescribed measuring process (Regulation (EC) 715/2007 in the currently applicable version).
- 3. Urban / extra-urban / combined. The figures shown were obtained in accordance with the prescribed measuring process (Regulation (EC) 715/2007 in the currently applicable version).



H bis ca. 558



Technical data

Engine

Model series OM651 DE22LA, Euro 6b N1 GR.III/N2 (MA6)

No. of cylinders / arrangement / valves 4 / in-line / 4

 Bore / stroke / displacement
 83 mm / 99 mm / 2143 cc

 Rated output
 100 kW (136 hp) at 3800 rpm

 Rated torque
 330 Nm at 1200 - 2400 rpm

Mixture preparation Electronically controlled direct injection with common rail, turbocharger and intercooler

Tank / electrical system

Tank capacity / fuel type approx. 70 l / Diesel / + approx. 11.5 L AdBlue

Battery 12 V / 92 Ah AGM battery

Alternator 14 V / 200 A

Performance / fuel consumption

Acceleration 0-100 km/h 12.8 sec Top speed 184 km/h

Fuel Consumption³ 7.1 / 5.4 / 6.0 \(\ell \) /100 km (with BlueEFFICIENCY package)

CO₂ emissions² 158 g/km (with BlueEFFICIENCY package)

Power transmission

Drive System Rear-wheel drive Clutch Converter

Transmission automatic 7-speed (7G-TRONIC PLUS)

Gear ratios 4.377 / 2.859 / 1.921 / 1.368 /1.0 / 0.820 / 0.728 Reverse 3.42 / 2.231

Final drive 3,267

Suspension

Front axle Independent suspension; MacPherson suspension with stabiliser, coil springs and shock absorber Rear axle Independent suspension; Semi-trailing arm rear suspension with coil springs and shock absorber

Wheels Light-alloy wheel; 6,5J X 16 ET52; Tyres 205 / 65 R 16C Steering Speed-sensitive electrically assisted power steering

Brakes Hydr. dual-circuit brake with vacuum booster; 4 disc brakes, front discs internally ventilated;

Dynamic control system ESP 9i® (Electr. Stability Program)

Weights in kg

Kerb weight¹ (FA / RA / total) 1113 / 687 / 1800

Payload 1250
Permissible axle loads (FA / RA) 1550 / 1650
Permitted GVW / GCW 3050 / 5050
Towing capacity, braked / unbraked 2000 / max. 750
Drawbar load / roof load max. 100 / max. 150

All prices and specifications are subject to change without prior notice. For a wider range of equipment and accessories available, please approach our sales specialists. All vehicles are covered by Cycle & Carriage with a 5-year Exclusive Warranty or 150,000 km, whichever is earlier from the date of registration. Prices quoted are inclusive of 6-months road tax, registration fee, number plates and GST, but without insurance. http://www.mercedes-benz.com.sg/vans

